

# DRYWALL SCREW FOR STEEL JOISTS, PHOSPHATED

## AREA OF USE


ESSVE Drywall screw is designed for the application of plasterboards indoors against light steel joists, drill capacity 0.4 - 0.9 mm.

## DESCRIPTION

The screw is produced by hardened carbon steel with phosfated or bright zinc plated surface. It is equipped with Philips crosshead Ph2.

## INSTALLATION INSTRUCTIONS

A screwdriver with a depth stop should be used for quick and efficient assembly. Recommended rpm: 25-50 mm 2800-6000/min.



Steel

Specification	
Surface treatment	Phosphated
Main Materials	Steel
Corrosion resistance class	C1
Application environment	Indoors



Standard Pro Pack										
Item no	Diameter	Length	Diameter of head	Thread length	Fixture thickness	Type of bits	Drill capacity min/max	Packaging	Contents	CE
521125	3,5 mm	25 mm	8,4 mm	20 mm	13 mm	PH2	0,4 - 0,9	ESSBOX 204	1000 PCS	✓
521142	3,5 mm	41 mm	8,4 mm	36 mm	26 mm	PH2	0,4 - 0,9	ESSBOX 304	900 PCS	✓
521150	3,5 mm	50 mm	8,4 mm	45 mm	39 mm	PH2	0,4 - 0,9	ESSBOX 304	500 PCS	✓