

# ACRYLIC SEALANT FLEX

## AREA OF USE

ESSVE Sealant AKRYL FLEX is a highly elastic acrylic sealant with high movement absorption.

- For use in dry, frost-free indoor and outdoor environments
- Indoor and outdoor joints
- Perfect as an acoustic joint
- Around doors and windows
- Penetrations, shadow gaps, etc.
- Maximum joint width: 25 mm
- Wet room approved XS2



## DESCRIPTION

Highly elastic acrylic sealant for interior joints requiring high movement absorption. Tolerates short-term storage in freezing temperatures down to -10°C. Easy to work with, water-soluble before curing. Use the ESSVE cartridge gun TACK GUN for easier application. Clean spills with water or a damp cloth.

- Does not crack
- Does not yellow
- Available in multiple NCS colors
- Weather-resistant
- Paintable
- Perfect as an acoustic joint
- Highly elastic
- Flexible
- Cleaned with water
- Application temperature +5°C to +40°C
- Store upright at room temperature, max +25°C

Specification	
Application environment	Indoors/Outdoors



Tillbehör		
Item no	Description	Contents
19997	NOZZLE STANDARD 300ML	5 PCS
19508	AIR GUN T22XP PRO METAL 600 ML	1 PCS
19315	ESSVE CAULKING GUN 300ML	1 PCS
19404	CAULKING GUN H14 PRO METAL	1 PCS
19504	AIR CAULKING GUN T16 PRO METAL 300 ML	1 PCS
19602	TACK GUN CAULKING TOOL 300ML	1 PCS
19201	SEALANT APPLICATION TOOL 6 MM	1 PCS
19202	SEALANT APPLICATION TOOL 8 MM	1 PCS
19203	SEALANT APPLICATION TOOL 10 MM	1 PCS
19204	SEALANT APPLICATION TOOL 15 MM	1 PCS
19205	SEALANT APPLICATION TOOL 20 MM	1 PCS
19206	SEALANT APPLICATION TOOL 25 MM	1 PCS
19207	SEALANT APPLICATION TOOL 30 MM	1 PCS
19944	CARTRIDGE NOZZLE 360°	5 PCS
19970	NOZZLE FLR 600ML-5	5 PCS
19999	NOZZLES FOR 600ML SAUSAGES - 5	5 PCS