

COIL COLLATED, WIRE COLLATED CLOUT NAILS 15°, HOT DIP GALVANIZED

AREA OF USE



ESSVE Clout nails are used to fasten roofing felt or other soft materials to the roof or wall. It is intended for use with roof felt, asphalt board, etc. outdoors. Longer dimensions are suitable for nailing board and drywall. Suitable for all standard tools for 15° plastic collated nails. NOTE! For min/max length, see each machine's product sheet.

DESCRIPTION

The nail is made of steel with a hot-dip galvanized surface finish for outdoor use, C3. It has a wide head designed to hold the felt in place and to prevent the nail from penetrating the material. Roofing nails are often used in combination with roof felt or wall felt to create a waterproof surface on the roof or wall. ESSVE roofing nails meet the CE requirement according to EN 14566:2008+A1:2009.

INSTALLATION INSTRUCTIONS

The nails are usually placed in a row with about 100-150 mm distance between each nail. It is important to place them at the right distance to avoid the felt coming loose or being damaged by rain and wind.



Specification	
Surface treatment	Hot Dip Galvanized
Corrosion resistance class	C3
Application environment	Outdoors



Standard Pro Pack

Item no	Diameter	Length	Diameter of head	Collation material	Packaging	Contents	CE
777665	3 mm	19 mm	9,5 mm	Wire	Cardboard box	2160 PCS	
777666	3 mm	22 mm	9,5 mm	Wire	Cardboard box	1920 PCS	
777432	3 mm	22 mm		Wire		7200 PCS	✓
10003216	3 mm	25 mm	9,5 mm	Wire	Cardboard box	1680 PCS	
10003214	3 mm	25 mm		Wire		7200 PCS	
777667	3 mm	32 mm	9,5 mm	Wire	Cardboard box	1200 PCS	✓
777434	3 mm	32 mm		Wire		7200 PCS	✓
777668	3 mm	38 mm	9,5 mm	Wire	Cardboard box	1080 PCS	✓
777436	3 mm	38 mm		Wire		7200 PCS	✓
777669	3 mm	45 mm	9,5 mm	Wire	Cardboard box	960 PCS	✓