

JOIST HANGERS, EXTERNAL FLANGES, HOT DIP GALVANIZED

AREA OF USE




ESSVE Joist hangers are designed to anchor timber beams and floor joists on the same level, both wood against wood and wood against concrete or masonry.

DESCRIPTION

Made of 1.5 or 2.0 mm Hot dip galvanized sheet steel. The joist hangers are equipped with 5 mm holes for nails/screws and 9 mm or 11 mm holes for bolts. There is also a 7 mm hole on the beam hanger flange that comes under the beam. The joist hangers are available in two designs partly with external flanges, Standard, partly with internal flanges, Type I.

INSTALLATION INSTRUCTIONS

Joist hangers are installed with e.g. ESSVE Anchor nails 4.0 mm or ESSVE Wood connector screws 5.0 mm. Joist hangers are fully nailed or nailed partly depending on the load. Bolt holes and appropriate fasteners, see Fasteners, are used when installing against solid or porous stone materials.



Specification	
Surface treatment	Hot Dip Galvanized
Corrosion resistance class	C2
Application environment	Outdoors



Standard Pro Pack						
Item no	Width	Height	Depth	Packaging	Contents	CE
453155	36 mm	142 mm	2 mm	Sticker label with barcode	1 PCS	
452268	40 mm	140 mm	2 mm		1 PCS	
452250	45 mm	97 mm	2 mm		1 PCS	
452252	45 mm	137 mm	2 mm		1 PCS	
452254	45 mm	167 mm	2 mm		1 PCS	
452278	45 mm	197 mm	2 mm		1 PCS	
452276	48 mm	95 mm	2 mm		1 PCS	
452274	48 mm	136 mm	2 mm		1 PCS	
451044	48 mm	166 mm	1,5 mm		1 PCS	✓
452280	48 mm	166 mm	2 mm		1 PCS	
452256	51 mm	135 mm	2 mm	Sticker label with barcode	1 PCS	
452258	51 mm	165 mm	2 mm		1 PCS	
452260	51 mm	195 mm	2 mm		1 PCS	
452270	60 mm	190 mm	2 mm		1 PCS	
452262	76 mm	152 mm	2 mm		1 PCS	
452272	90 mm	145 mm	2 mm		1 PCS	
452266	100 mm	140 mm	2 mm		1 PCS	
453148	115 mm	162 mm	2 mm		1 PCS	
453154	140 mm	180 mm	2 mm		1 PCS	