

SELD-DRILLING SCREW WITH BONDED WASHER, CORRSEAL

AREA OF USE


ESSVE Self-drilling screw with bonded washer designed for installing the sheet-metal on beams, sheet-metal on light beams, etc., indoors/outdoors.

DESCRIPTION

The screw is produced in hardened carbon steel with bright zinc plated or C4 class Silver CorrSeal surface treatment. Fitted with hex head.The screw has a bonded washer with EPDM rubber. The screw is self drilling and tapping.

INSTALLATION INSTRUCTIONS

Ensure that the screw is not overtightened during installation to prevent damage to sealing washer. A screwdriver with adjustable depth stop should be used for quick and efficient installation. Recommended speed: 1800-2500/min.



Steel

Specification	
Surface treatment	CorrSeal
Main Materials	Steel
Corrosion resistance class	C4
Application environment	Outdoors



Standard Pro Pack									
Item no	Diameter	Length	Diameter of head	Thread length	Socket	Drill capacity min/ max	Packaging	Contents	CE
63534	6,3 mm	38 mm	15 mm	20 mm	8 mm	6 - 16	ESSBOX 304	200 PCS	✓
63536	6,3 mm	50 mm	15 mm	32 mm	8 mm	6 - 16	ESSBOX 304	200 PCS	✓
63538	6,3 mm	65 mm	15 mm	47 mm	8 mm	6 - 16	ESSBOX 304	100 PCS	✓
63540	6,3 mm	90 mm	15 mm	72 mm	8 mm	6 - 16	ESSBOX 304	100 PCS	✓
63833	5,5 mm	25 mm	10 mm	13 mm	8 mm	1,5 - 6	ESSBOX 304	200 PCS	✓
63835	5,5 mm	32 mm	10 mm	13 mm	8 mm	3 - 12	ESSBOX 304	200 PCS	✓