


MOULDING/BASE/FLOOR SCREW SMALL HEAD FOR WOODEN AND STEEL JOISTS, YELLOW CHROMATE

AREA OF USE

ESSVEMoulding/base and floor screw designed for the installation of mouldings base boards and solid pine floors indoors, against wood or steel joists. Drill capacity 0.4 – 0.9 mm. For installation of harder wooden floors e.g. oak pre-drilling is necessary.



DESCRIPTION

The screw is produced in hardened carbon steel with yellow chromate surface treatment and in yellow chromate or white finish. The screw has a counter-thread under the head to press mouldings base boards and solid pine flooring against the substrate. The screw is fitted with a fibre cut in the point to reduce cracking and reduce the drive-in torque. The small head gives a good countersink and the screw is fitted with TX-drive/bits.

INSTALLATION INSTRUCTIONS

Recommended rpm: 400-1200/min.

Specification

Surface treatment	Yellow zinc plated
Main Materials	Steel
Corrosion resistance class	C1
Application environment	Indoors

C1

Small Pack

Item no	Diameter	Length	Diameter of head	Thread length	Type of bits	Drill capacity min/max	Packaging	Contents
10003690	3,9 mm	42 mm	5 mm	25 mm	TX10	0,4 - 0,9	Zip-lock poly bag 7 cm	20 PCS
10003691	3,9 mm	57 mm	5 mm	35 mm	TX10	0,4 - 0,9	Zip-lock poly bag 7 cm	20 PCS