

UNIVERSAL PLUG GREENFIX WITH SCREW

AREA OF USE

ESSVE Universal Plug GreenFix is manufactured from over 80% recycled nylon. The plug is ideal for use in concrete, brick, aerated concrete, lightweight aggregate, hollow brick, and board materials.

Aerated concrete and lightweight aggregate are also known as Leca, Fibo, Ytong, Siporex, etc.

DESCRIPTION

ESSVE GreenFix is a universal plug offering high load capacity and secure anchoring, even when the base material is unknown.

In solid materials, the plug expands to achieve a strong hold, while in hollow materials it forms a reliable knot behind the surface to create a safe anchorage.

The plug features anti-rotation ribs that prevent spinning in the drilled hole, and the collar stops it from being pushed too far in. The result is quick, safe, and trouble-free installation across a wide range of applications.

GreenFix is also available in small packs with matching screws, where the screw dimensions are selected according to the plug's load tables.

INSTALLATION INSTRUCTIONS

Drill a hole with the same diameter as the plug. Gently tap the plug in until it is flush with the surface. Use a screw with the correct dimension and a length slightly longer than the plug plus the thickness of the fixture.




Concrete



Plaster board



Hollow brick



Lightweight concrete



Brick

Small Pack

Item no	Diameter	Length	Fixture thickness	Drill bit diameter	Drill depth	Suitable screw	Type of bits	Packaging	Contents
10005290	5 mm	30 mm	5 mm	6 mm	40 mm	4,0 - 5,0	TX25	Zip-lock poly bag 12cm	10 SET
10005291	6 mm	40 mm	15 mm	8 mm	50 mm	4,5 - 6,0	TX30	Zip-lock poly bag 12cm	10 SET
10005292	5 mm	30 mm	5 mm	6 mm	40 mm	4,0 - 5,0	TX25	Zip-lock poly bag 12cm	10 SET
10005293	6 mm	40 mm	15 mm	8 mm	50 mm	4,5 - 6,0	TX30	Zip-lock poly bag 12cm	10 SET